

CNC ENGRAVING & ROUTER MACHINE-2D/3D



Features

- Original HSD Italian Spindle Gives you Trouble free Performance for long Time Work
- Table is Cover with PVC Rigid
- Axis Drive System : X, Y Rack & Pinion & Z ball Screw
- Hiwin Linear Guide for High Accuracy & For Long Period of Time



Specifications

Model	AP-6590	AP-1212	AP-1325	AP-1530
Working Area (X,Y, Z)	650 x 900 x 100 mm	1200 x 1200 x 200mm	1300 x 2500 x 200 mm	500 x 3000 x 200 mm
Spindle	1.2 KW Air Cooled,(HSD Italian)	3 KW Air Cooled,(HSD Italian]	6 KW Air Cooled,(HSD Italian]	6 KW Air Cooled, (HSD Italian]
Spindle Speed	18000 RPM	18000 RPM 2	18000 RPM	18000 RPM
Distance Between Bed &Gentry	130 mm	200 mm	200 mm	200 mm
Maximum Travelling Speed	10 mtr/min	18 mtr/min	18 mtr/min	18 mtr/min
Cutting Tool Diameter	03 to 010 mm	03 to 014 mm	03 to 016 mm	03 to 016 mm
Repeated Location	0.035 mm	0.025 mm	0.025mm	0.025 mm
Operating System	DSP-Hand Held Controller	DSP-Hand Held Controller	DSP-Hand Held Controller	DSP-Hand Held Controller
Driving System	Stepper Motor	Stepper Motor	Stepper Motor	Stepper Motor
Power Supply	AC 230V/1PH	AC 420V/ 3PH	AC 420V/3PH	AC 420V/3PH

SAMPLES



Optional Items

